



PART NUMBERS

319023	5-Gallon Pail (White)
319024	5-Gallon Pail (Black)

TECHNICAL DATA

Color	White & Black
Consistency	Medium Viscosity
Base	Synthetic latex
Solvent	Water
Weight per Gallon	9.65 lbs. (+/- 0.2)
Solids Content	55 % (+/- 2%)
Viscosity	>15,000 cps
Coverage	Smooth: 200- 600 sq. ft./gal Porous: 75- 175 sq. ft./gal
Dry Time (to touch)	1 – 2 Hours
Service Temperature	-20°F to 200°F
Mildew Resistance	Mold & Mildew resistant
VOC	Exempt: 0 g/l Non-Exempt: 13 g/l (less water)
Packaging	5 gal. pails
Specifications Compliance	LEED Compliant SCAQMD Rule 1168 Passes ASTM E-84, ASTM G-21

PRECAUTIONS

Inspect all winter shipments on arrival. Do not allow this product to freeze. Apply when temperatures will not fall below freezing for 36-48 hours. Do not apply this product where temperatures will exceed 200°F. Keep out of the reach of children. Review Material Safety Data Sheet for complete safety information prior to use.

For Industrial Professional Use Only.

APPLICATION

Temperature	40°F to 110°F (4.4°C to 44°C)
Method	Prior to Application, mix thoroughly to achieve a uniform consistency Apply to all surfaces by brush, roller or airless spray. Application rate will vary depending on porosity of the insulation. Apply one coat by airless spray, or two coats by brush or roller. RE-500 can be applied using HVAC Robotic Spray Applicators. Prior to turning on the air handler verify the product is thoroughly dry.
Surface Preparation	Lined air duct should be mechanically cleaned to remove all mold, dust and loose particulate being careful not to damage insulation or liner. Galvanized surfaces need to be clean of all accumulated mold, dust and loose particles. Ensure that all interior surfaces are thoroughly dry before application of the RE-500. RE-500 may be applied directly onto cleaned, unruined galvanized surfaces. Please review all pertinent ASHRAE and ANSI publications. Consult an Indoor Air Quality Environmentalist and the local building codes prior to starting the remediation project.
Clean Up Wet	Soap and Water
Clean Up Dry	UN-TACK™ or Solvent (Use safe handling practices)

STORAGE

Temperature	.40°F to 110°F (4.4°C to 44°C)
Shelf Life	One year (unopened)
Flammability	Non-flammable

